


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Corner originally set in 1863 by David T. Thompson, under government contract number 103. Surveyor General notes state;

Set post for corner to sections 13, 14, 23, 24, in a mound of stone, on steep hillside.

No record of resurvey found in the record.



Description of corner evidence found:

Found mound of stone.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Gregory T. Blackman

OREGON
JULY 13, 1973
GREGORY T. BLACKMAN
991

Description of monument and accessories I established to perpetuate the original location of this corner I set a 2 inch by 36 inch galvanized pipe with brass

cap, marked as shown in the mound of stone, and raised a mound of stone, from which New BT'S.

A pine 12 inches in diameter, bears N 9 E, 30.9 feet dist., Marked T3S R 40 E S 13 BT.


A pine 15 inches in diameter bears N 65 W 39.7 feet dist. , Marked T3S R 40 E S 14 BT.

A pine 12 inches in diameter bears S 38 W, 69.5 feet dist., Marked T 3 S R 40 E S 23 BT?

A pine 12 inches in diameter bears S 67 E, 37.6 feet dist., Marked T 3 S R 40 E S24 BT.

I used a steel tape and a magnetic compass with 20 degrees East declination set into the compass.

See survey number 46-79



Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office for record on the day of

..... by
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR

Date Received 4-19-84

Date Filed 4-19-84

By G. LANGLITZ, DEPUTY

File No. 845-84R

GPO 796:333

HORIZONTAL CONTROL DATA

UNION COUNTY, OREGON

OREGON STATE PLANE, NORTH ZONE (3601)

STA NAME: 200136

CORNER COMMON TO: 13,14,23,24

TWP. 3 S. RGE. 40 E.

GEODETIC COORD: NAD 83(91)

DATE TIED: 12 MARCH 2001

LAT: 45 ° 17 ' 49.14839 " N

SURVEYOR: GREGORY T. BLACKMAN
OPLS 991

LONG: 117 ° 46 ' 2.55856 " W

FIRM: BAGETT, GRIFFITH, & BLACKMAN
2006 ADAMS AVENUE
LAGRANDE, OR 97850
(541) 963-6092

SP. COOR: NAD 83(91)

N: 606259.081 INT FT.

E: 8905117.328 INT FT.

TYPE: GPS

THETA: 1 ° 56 ' 16.5759124 "

ORDER: SECOND CLASS: 1

SCALE FACTOR: 0.9998970814


ELEV: 3899.85 US FT.

ELEV: DATUM: NGVD 29

COMMENTS:

Brass cap is in down fencline. Tripod set up possible, poor visibility see obstruction sheet.

14	13
23	24



Renewal Date: Dec. 31, 2001

1 METER = 3.2808333333... US FEET = 39.37 INCHES

1 METER = 3.280839895 INT'L FEET OR 1 INCH = 2.54 CM

TO CALCULATE ELEVATION FACTOR (IN THE NORTH AMERICAN CONTINENT)

DIVIDE 20,906,000 BY (20,906,000 + ELLIPSOID ELEV. IN FEET)