
## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally established by Alonzo Gesner under GLO contract number 683, dated June 7, 1880. Surveyor General record states:

Set basalt stone 22x10x6 in 17 inches in the ground on sidehill sloping West for  $\frac{1}{4}$  sec cor marked  $\frac{1}{4}$  on the North side, from which;

A red fir 6 in diam bears N8°E, 16 lks dist marked ¼ S18 BT A red fir 26 in diam bears S26°W, 28 lks dist marked ¼ S19 BT



No record of subsequent monumentation found in Union County survey records.

Description of corner evidence found:

Found a stone 21x10x5 inches with chisel marks visible.
Found no evidence of the original Northeast bearing tree.
Found a root hole S26°W, 28 lks.

See map of survey dated August, 1988.

UNION COUNTY SURVEYOR	
Date Received 9-15-88	
Date Filed <u>9-15-88</u>	
BY G. LANGLITZ DERLITY	
File No. 122-88 R	

Description of monument and accessories I established to perpetuate the

original location of this corner: In place of the found original corner stone, I set a  $2\frac{1}{2}$ " x 30" aluminum pipe with aluminum cap marked as shown, 28 inches in the ground, from which:

New BTs:

A 12 inch diameter Douglas Fir bears S66°W, 8.03 feet marked ¼ S19 BT A 11 inch diameter Western Larch bears N59°W, 23.35 feet marked ¼ S18 BT

Raised a mound of stone around monument, 2 ft. base to top of cap.


Buried the original corner stone West and alongside of monument.

Painted a 6 inch red band around all BTs and attached 54-3 and 54-9 signs.

Set a steel fencepost approximately 5 feet East with 54-9 sign attached.

I hereby certify that the above corner point was perpetuated as hereon described on August 5, 1988.

Witnesses: Rick Robinson and Jeff Petersen



REGISTERED
PROFESSIONAL
LAND SURVEYOR

PREGON
JULY 10, 1964
DUANE I. GRIFFITH
644

I used a steel tape and magnetic compass in the establishment of new accessories. I used 18° East magnetic declination and the distances are to a 50d spike driven in the right side of the root crown. I attached a brass washer marked OPLS 644 to the BT blaze.

Office of County of	
State of, / hereby certiff for record on the day of	y that the within instrument was filed in this office
	by(DEPUTY)

Form R6-7100-57 (9/71)

☆U.S. GOVERNMENT PRINTING OFFICE-1983-793-276