

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Index: E-11

Quarter Corner Sections 4 and 9, T.4S., R.35E., W.M.

Original corner was set by Rufus Moore under Contract No. 451 dated June 12, 1882.

His record reads:

Set a basalt stone 18x10x6 in 12 ins. in ground for 1/4 sec. cor. marked 1/4 on N face.

From which:

A Pine 18" ins. in dia. bears S32°E 7 lks. dist. marked 1/4 S BT.

A Pine 16" ins. in dia. bears N34°E 17 lks. dist. marked 1/4 S BT.

1	DIAGRAM	1
1		1
1		1
1		1
1	T4S R35E	1
1	S4	1
1	1/4-----	1
1	S9	1
1	1993	1
1	ORLS 852	1
1		1

Description of corner evidence found:

Found a 6' high 12" dbh buckskin Ponderosa Pine snag scribed 1/4 S BT. From which:

A 18x10x6 inch basalt stone with top exposed 3 inches bears S34°W, 11.2'. Dug the stone out and found a clearly chiseled 1/4 on the north face.

Description of monument and accessories I established to perpetuate the original location of this corner:

In the position of the found stone corner, I set a 2 1/2" x 30" aluminum pipe with aluminum cap. I buried the stone along side of the pipe.

I stamped the cap as shown in the diagram above. I set the following new witness trees:

A 14" dbh Western Larch bears N10°00'E, 34.6', scribed 1/4 S9 BT.

A 14" dbh Douglas Fir bears S31°00'E, 26.2', scribed 1/4 S9 BT.

A 18" dbh Douglas Fir bears N51°30'W, 46.1', scribed 1/4 SB BT.

A 16" dbh Douglas Fir bears S48°45'W, 16.0', scribed 1/4 SB BT.

An aluminum washer stamped RLS 852 is nailed between the letters B and T on each new tree. All the BT's have BT signs attached.

This work was done June 23, 1993.

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

David L. Haddock

**OREGON
JULY 12, 1900
DAVID L. HADDOCK
852**

Office of _____ County of _____
State of _____, I hereby certify that the within instrument was filed
in this office for record on the _____ day of _____, 19____.

(COUNTY OFFICIAL)

(DEPUTY)

**UNION COUNTY
SURVEYOR**

Date Received 9/1/93

Date Filed 9/10/93

By [Signature]

File No. 041-193R