

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:
Corner has not been previously set.

DIAGRAM

T4S R35E

NW1/16 S 7

1989
PLS 699

Description of corner evidence found:
Corner is being set by this survey.

UNION COUNTY SURVEYOR	
Date Received	<u>9-25-89</u>
Date Filed	<u>9-25-89</u>
By	<u>G. LANGLITZ</u>
File No.	<u>174-89 R</u>

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 2 1/4" aluminum cap, marked as shown in the diagram, 22" in the ground to solid rock, at a point as determined by the procedures set forth in the MANUAL OF INSTRUCTIONS FOR THE SURVEY OF PUBLIC LANDS for the subdivision of sections. Built a mound of rock to be 38" in diameter by 8" high around the monument, from which a new BT is:

14" Ponderosa pine bears S30° 30'E, 216.6 feet scribed NW1/16 S7 BT

No. 4 Rebar with a yellow plastic cap marked PLS 699 bears N87° 30'E, 27.3 feet.

Attached BT and Land Survey Monument signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being the bearing between the SE and S 1/4 corners of Section 7 as shown on MOS 43-76, to stamped brass washers nailed in the scribed red-painted blazes. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 5 feet N and 5 feet E of the corner on the National Forest boundary lines. Attached Forest Boundary signs to each post and a Land Survey Monument sign to the N post.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877, do hereby certify that on July 19, 1989, I established the corner as herein described.

FILED

IN THE OFFICE OF THE UNION COUNTY SURVEYOR

THIS _____ DAY OF _____, 19____

Union County Surveyor

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 9, 1965
LELAND LEE MYERS
699