

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

---

History of original corner establishment:

Index: G-13

Quarter Corner Sections 9 and 10, T.4S., R.35E., W.M.

Original corner was set by Rufus Moore under Contract No. 451 dated June 12, 1882. His record reads:  
 40.00 Set a basalt stone 20x15x10 15 ins. in ground for 1/4 sec. cor. marked 1/4 on W. face and raised a mound of stone alongside. Fits impracticable.

1	DIAGRAM	1
1	T4S R35E	1
1	1/4	1
1	S9:S10	1
1	1993	1
1	PLS 852	1
1		1
1		1
1		1


Description of corner evidence found:

Found 20x15x10 inch stone with chiseled 1/4 on face. Stone was imbedded in ground at bottom of rockjack along intersecting south fenceline and east-west fencelines.


Description of monument and accessories I established to perpetuate the original location of this corner:

In the position of the found stone corner, I set a 2 1/2" x 30" aluminum pipe with aluminum cap. I buried the stone along side of the pipe. I stamped the cap as shown in the diagram above. I set the following 2" diameter aluminum caps on 1/2 inch by 24 inch rebar for reference monuments:  
 S86 1/4°W, 18.7 feet near a rockjack at opposite end of gate.  
 S7 1/4°W, 9.3' near large rock under south fenceline.  
 N84°E, 29.2' under east fenceline.  
 N 0 1/4°W, 18.7' near underground powerline vault.

This work was done July 7, 1993.



*David L Haddock*



Office of \_\_\_\_\_ County of \_\_\_\_\_  
 State of \_\_\_\_\_, I hereby certify that the within instrument was filed  
 in this office for record on the \_\_\_\_\_ day of \_\_\_\_\_, 19\_\_\_\_.

( COUNTY OFFICIAL )

( DEPUTY )

