


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:
Corner not previously established.



Description of corner evidence found:

None

UNION COUNTY SURVEYOR	
Date Received	<u>12-5-85</u>
Date Filed	<u>12-6-85</u>
By	<u>G. LANGLITZ, DEPUTY</u>
File No.	<u>160-85R</u>

See map of survey dated November 1985.

Description of monument and accessories I established to perpetuate the original location of this corner: At position determined by survey I set a 2 1/2"x30" aluminum pipe with aluminum cap marked as shown 28 inches in the ground, from which:


A 14" Tamarack bears N25°E, 52.60 feet, marked C 1/4 S24 BT

A 12" Douglas Fir bears N64°W, 36.08 feet, marked C 1/4 S24 BT

Set a steel fence post approximately 5 feet South with 54-9 sign attached.

Corner set 10/15/85

Witness: Greg Blackman, Rick Robinson, Stratton French



REGISTERED PROFESSIONAL LAND SURVEYOR

OREGON
JULY 10, 1964
DUANE I. GRIFFITH
644

Brass washer nailed to BT blaze. Used steel tape and magnetic compass with 20° East declination. Measured to 50d spike set in right side of tree when facing tree, unless otherwise stated.

Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by
(COUNTY OFFICIAL) (DEPUTY)