


47-1971

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

V-11

History of original corner establishment:

Original survey by GLO contract.
The original notes state;
N 89°47'W on true line between Sections 28 and 33;
40.26 ch. set a basalt stone 12x10x6 ins. 8" in ground for
1/4 cor. marked on N face from which;
A fir 12" in diam bears N40°E 34 lks dist marked 1/4 SBT
A fir 4" in diam bears S48°E 12 lks dist marked 1/4 SBT



Description of corner evidence found:

In section 28 found a down fir with scribe
In section 33 found slab with scribe

Description of monument and accessories I established to perpetuate the original location of this corner

At the position of the corner a new road is to be built and a monument was not placed at this time. The monument to placed after clearing and road construction

From the position of the corner two new bearing trees were established to reference the corner.

A white fir 10" in diam bears N67°W a distance of 35.9 feet marked 1/4 SBT

A doug fir 14" in diam bears S43°W a distance of 43.3 feet marked 1/4 SBT

The distance measured to center of respective trees on the level. USFS bearing tree signs were placed on the bearing trees breast high facing the corner. The bearing trees were painted with red strip and blaze painted.

REGISTERED
OREGON
LAND SURVEYOR

James G. Voelz

MAY 4, 1968
JAMES G. VOELZ
301

Office of.....County surveyor..... County of..... Union
State of..... Oregon....., I hereby certify that the within instrument was filed in this office
for record on the 26 day of July 1971, at 8 o'clock a.m., (signed)
.....County surveyor..... by *James G. Voelz*
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR	
Date Received	_____
Date Filed	_____
By	_____
File No.	497-84R

1261-1971