

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**


**Adams & Clark, Inc.  
1720 W. Fourth Ave.  
Spokane, WA 99204-1702**

Corner Code A-1  
Township 4 South, Range 39 East

**History of original corner establishment:**

Original U.S. General Land Office Survey, 1863, states:

"80.00 chains. Set post common to Sec. 1, 6, 31 & 36 and Townships 3 & 4 South, Ranges 38 & 39 East. Made mound of earth depositing charred stake as per instructions."



**Description of corner evidence found:**

Found 2" Iron Pipe filled with concrete with cross head brass screw set in concrete per Maps of Survey 12-62, 67-74, 27-90, and 19-80, with no identifying cap or tag.  
Also found 6"x4" stone 8" out of ground, S78°50'49"W 33.73'.  
Also found 5/8" rebar with no identifying cap or tag, N16°02'26"W 122.04'

Refer to Union County Survey Records.

**Description of monument and accessories I established to perpetuate the original location of this corner.**

Accessories:

Set 5/8"x24" rebar with yellow plastic cap marked "RP LS 1503":

- N77°29'09"E 29.34'
- S15°31'26"E 28.76'
- S35°17'54"E 29.18'

Accessory ties were made with electronic total station theodolite, and steel tape.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Leslie D. Killingsworth*

OREGON  
JANUARY 18, 1974  
LESLIE D. KILLINGSWORTH  
1503

RENEWAL DATE:  
6/30/2003

**UNION COUNTY  
SURVEYOR**

Date Received 12/22/15

Date Filed 12/22/15

By [Signature]

File No. 191-2015R

Leslie D. Killingsworth, P.L.S. 1503

11/07/2002  
Date

**HORIZONTAL CONTROL DATA**  
**UNION COUNTY, OREGON**  
**OREGON STATE PLANE, NORTH ZONE (3601)**

STA NAME: 200608

SECTION CORNER COMMON TO SECTIONS 31, 36, 1 and 6

TWP. 3 S. RGE. 38 E.  
& 4 & 39

DATE TIED: October 12, 2006

SURVEYOR: RICK G. ROBINSON  
OPLS 2219

GEODETIC COORD: NAD 83(91)

LAT: 45 ° 15 ' 11.24902 " N

LONG: 117 ° 59 ' 37.19356 " W

FIRM: BAGETT, GRIFFITH, & BLACKMAN  
2006 Adams Avenue  
La Grande, OR 97850  
(541) 963-6092

SP. COOR: NAD 83(91)

N: 588388.135 INT FT.

E: 8847416.217 INT FT.

TYPE: GPS

THETA: 1 ° 46 ' 38.8481624 "

ORDER: SECOND CLASS: 1

SCALE FACTOR: 0.9998956643


ELEV: 2715.45 US FT.

ELEV: DATUM: NGVD 29

---

COMMENTS:

Corner is a 1 1/2" concrete filled pipe with  
a brass screw



Renewal Date: December 31, 2006

1 METER = 3.280833333... US FEET = 39.37 INCHES

1 METER = 3.280839895 INT'L FEET OR 1 INCH = 2.54 CM

TO CALCULATE ELEVATION FACTOR ( IN THE NORTH AMERICAN CONTINENT)

DIVIDE 20,906,000 BY (20,906,000 + ELLIPSOID ELEV. IN FEET)