

60-69A


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

53

History of original corner establishment:

Original survey by General Land Office contract survey 1882.

The original notes state; Set a basalt stone 17x8x7 ins
12 ins in ground marked † on N face from which;
A pine 18" in diam bears S22°E 60 lks dist marked † SBT;
A pine 36" in diam bears N22°E 44 lks dist marked † SBT;



Description of corner evidence found:

Found- a pine snag 26" in diam bears N22°E 60 lks dist;
Found- a pine stump 25" in diam bears S22°E 44 lks dist with scribe;
Original bearing trees are no longer satisfactory.




Description of monument and accessories I established to perpetuate the original location of this corner

At the position of the corner I set a 2" galvanized pipe 30" long with bronze cap on top and 8" plate welded to bottom. Pipe set 6" deep on rock and raised a stone monument.

I stamped the disk

From the monument the original bearing trees are none;
I set two new bearing trees as follows;
A pine 9" in diam bears N15°E 26.5 ft dist marked † SBT;
A pine 16" in diam bears S20°W 63.5 ft. dist marked † SBT;
Distance measured to center of trees and marked with scribe.
I set a steel fence post with USFS sign 54-4 attached.
National Forest boundary signs were placed on the post indicating National Forest land to North and East. Bearing tree signs were placed on the bearing trees shoulder high facing the corner.



Office of County surveyor County of Union
State of Oregon I hereby certify that the within instrument was filed in this office
for record on the 11 day of Sept 1969, at 2 o'clock p. m., (signed)
..... County Surveyor by James G. Voelm
(COUNTY OFFICIAL)

UNION COUNTY SURVEYOR
Date Received _____
Date Filed _____
By _____
File No. <u>609-84R</u>