

72-69A


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

64

History of original corner establishment:

Original survey by General Land Office contract survey 1882
The original notes state. Set a basalt stone 18x9x5 from which.
No bearing trees given.; raised a mound of stone.

R-23



Description of corner evidence found:

Found a mound of stone but could not find marked stone.


REGISTERED
OREGON
LAND SURVEYOR

James G. Voelz
MAY 4, 1953
JAMES G. VOELZ
381

Description of monument and accessories I established to perpetuate the original location of this corner:

At the position of the mound I set a 2" galvanized pipe 30" long with bronze cap on top and 8" plate welded to bottom. The pipe set to a depth of 24".

I stamped the disk



From the monument the bearing trees are;

A black pine 18" in diam bears N33°E 192.4 ft. dist marked 1/4 SBT

A black pine 15" in diam bears S14°E 474.3 ft. dist marked 1/4 SBT;

Distance measured to center of trees and marked with a scribe.

I set a steel fence post with USFS sign 54-4 attached. USFS bearing tree signs were placed on the bearing trees shoulder high facing the corner.

Office of..... County surveyor..... County of..... Union
State of..... Oregon....., I hereby certify that the within instrument was filed in this office.....
for record on the 13 day of Sept....., 1969, at 8 o'clock A.M., (signed)
..... County surveyor..... by *James G. Voelz*
(COUNTY OFFICIAL)

UNION COUNTY SURVEYOR
Date Received _____
Date Filed _____
By _____
File No. 619-84R