


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. T-13

History of original corner establishment:

In 1882, under Contract No. 451, Rufus S. Moore set a post, from which a 10" Pine bears N35°W, 81 lks. and a 34" Pine bears S65°E, 98 lks.



Description of corner evidence found:

Found 12" Pine, dead and down, blazed and scribed, "1/4 S BT" bears N35°W, 81 lks from corner.

Description of monument and accessories | established to perpetuate the original location of this corner:

Cap is stamped:

Corner set from evidence.
Set 2.5"x30" aluminum capped aluminum pipe rising 14" above ground in mound. Set steel fence post 3.0 ft. north of corner.

T5S R35E
1/4
S28 | S27
RLS 1844
1985

New BT's:

- 5.5" P. Pine bears N45°W, 59.3 ft., blazed & scribed: 1/4 S28 BT.
- 6" W. Larch bears N52.5°E, 104.6 ft., blazed and scribed: 1/4 S27 BT.

Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982. Brass disk stamped "LS 1844" nailed to lower end of blazes.

Corner is on slight south slope at the north end of a logged area. Take Road 5155040 to Road 5155043 to clear cut at top of ridge. Dirt road runs north 200 ft. to corner.

Compass Declination: 19 1/2°E
Witness: Bernie Sutton

I hereby certify the above described corner monument and/or accessories was established as described on April 12, 1985.



Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY SURVEYOR

Date Received 9-18-85

Date Filed 9-23-85
☆ GPO-798-276

By G. Langholz DEPUTY

File No. 70-85 R