


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

In 1882, under Contract No. 451, Rufus S. Moore set a post, from which a 9" Pine bears N68°W, 19 lks and a 9" Pine bears S62°E, 16 lks.

Index File No. T-21



Description of corner evidence found:

No corner monument or other evidence found.

Description of monument and accessories established to perpetuate the original location of this corner:

Cap is stamped:

T5S R35E  
1/4  
S26 | S25  
RLS 1844  
1985

Corner set by single proportioning. Set 2.5"x30" aluminum capped aluminum pipe rising 6" above ground. Set steel fence post 3.0 ft. north of corner.

2 iron bars, 36"x5/8", with aluminum caps set for Reference Monuments:

S31 1/5°W, 71.0 ft.

S60°E, 59.0 ft.

Cap is stamped: RM

Cap is stamped: RM

S 26  
RLS 1844  
1985

S 25  
RLS 1844  
1985

Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982. Brass disk stamped "LS 1844" nailed to lower end of blazes.

Corner is between the Grande Ronde River and Sheep Creek, 4000 ft. south of the intersection of Road 51 and Rd 5125.

Compass Declination: 19 1/2°E

Witness: Bernie Sutton

I hereby certify the above described corner monument and/or accessories was established as described on May 5, 1985.



Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

(COUNTY OFFICIAL)

(DEPUTY)

**UNION COUNTY  
SURVEYOR**

Date Received 9-18-85

Date Filed <sup>☆ GPO-798-276</sup> 9-23-85

By G. LANGLITZ, DEPUTY

File No. 74-85 R