


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHED:

Corner not previously established.

T 5 S R 38 E G-14



DESCRIPTION OF CORNER EVIDENCE FOUND:

None.

SEE SURVEY 035-2020

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO MONUMENT THE ORIGINAL LOCATION OF THIS CORNER:

At position by survey I set a 5/8" x 30" iron pin, 27" in the ground, with 2 1/2" aluminum cap marked as shown below,
From which:


NEW BEARING OBJECTS:

An 8" Lodgepole Pine bears South 5° East a dist. of 8.80 ft., marked CW 1/16 S10 BT.
A 14" Lodgepole Pine bears North 58° West a dist. of 8.65 ft., marked CW 1/16 S10 BT.

Set steel fence post approx. 1 ft. North.

I hereby certify that the corner was monumented on September 23, 2020.

Witness: Kyle A. Tucker



I used a steel tape and magnetic compass in the establishment of the new accessories. I used 14° East declination, the distances are to a 60d spike driven into the right side of the root crown of the bearing trees. A brass washer marked OPLS 83571 is attached to the BT blaze of the new bearing trees.

REGISTERED
PROFESSIONAL
LAND SURVEYOR



OREGON
June 2, 2010
JEFFREY S. HSU
83571

Renewal Date: June 30, 2021

UNION COUNTY
SURVEYOR

Date Received 10/12/2020

Date Filed 10/12/2020

Filed By J.S.H. DEPUTY

File Number 072-2020R