CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This section corner was set by deputy surveyor Timothy W. Davenport, under Contract No. 102, dated July 20, 1863. He states he set a post for corner to Sec's 24, 25, and 19, 30. Made mound of earth and drove charred stake as per instruction.

DIAGRAM

T 5 S
R 38 E | R 39 E
S 24 | S 19
S 25 | S 30
1987
ORLS 645

Description of corner evidence found:

At the assumed section corner location I found no trace of the original corner. Spring branch that is South 3.40 chains has no definite thread; it spread out too much so could not use this GLO call to restore this corner.

Description of monument and accessories I established to perpetuate the original location of this corner:

With no acceptable evidence of the original corner I then established the section corner by single proportioning. I then set an Alum. cap on a 2" x 30" pipe, with a magnet fixed in the cap, at the corner location. I buried the pipe flush with the surface of the ground. I then placed a small mound of stone 2½ feet dia. 6" high covering the monument, from which I set two bearing trees:
A pine 23" dia. bears S 07 45 W, 123.38 feet and scribed T 5 S R 38 E S 25 BT.
A pine 23" dia. bears S 39 17 E, 83.23 feet and scribed T 5 S R 39 E S 30 BT.

No other trees are available.

UNION COUNTY SURVEYOR
Date Received 9-22-87
Date Filed 9-25-87
By G. LANGLITZ, DEPUTY
File No. 134-87 R

REGISTERED PROFESSIONAL LAND SURVEYOR
James H. Hambleton
9-25-87
OREGON JULY 10, 1964
JAMES H. HAMBLETON
645

REFER TO SURVEY 28-87

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....
..... *by* .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆GPO—798-276

1