24-6 91

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

9

1
E-25

History of original corner establishment:

Original survey by contract survey in 1882
The original notes read; Set a basalt stone 18x18x6 to corner of section 1,6,12 and 7 of T6S R35½E , R36E, from which; A pine 24" in diam bears N35°E 80 lks dist marked T6S R36E S6BT.
A pine 36" in diam bears S20°E 16 lks dist. marked T6S R36E S7BT.;
A pine 24" in diam bears S40°W 64 lks dist marked T6S R35½E S12BT.;
A pine 36" in diam bears N60°W 28 lks dist marked T6S R35½E S1 BT.

DIAGRAM

T6S
R35½E | R36E
S1 | S6
S12 | S7

Description of corner evidence found:

In section 6 a 24" stump was found with scribe
In section 7 a log 23" in diam
In section 12 a 22" down pine log with full scribe visible.
In sectionl found a down 30" pine with scribe visible.
We could not find the stone.

REGISTERED
OREGON
LAND SURVEYOR
James G Voelz
MAY 4, 1956
JAMES G. VOELZ
381

Description of monument and accessories I established to perpetuate the original location of this corner

Set a 2" galvanized pipe 30" long and 24" in the ground with bronze cap and 8" plate welded to bottom. The hole was back filled with stone and tamped soil.

I marked the disk.

COR
T6S
R35½E R36E
S1 | S6
S12 | S7
ORE LIC 381
1969

A pine stump 24" in diam bears N35°E 80 lks dist.
A down pine log 23" in diam bears S20°E 16 lks dist.
A down pine log bears S40°W 64 lks dist.
A down pine log 30" in diam bears N60°W 28 lks dist; I also established four new BT'S;
A pine 7" in diam bears N 17°E 31.7 ft. marked T6S R36E S6BT.
A fir 12" in diam bears S4°E 35.7 ft. dist marked T6S R36E S7BT.
A fir 15" in diam bears S79°W 41.6 ft. dist marked T6S R35½E S12BT.
A pine 12" in diam bears N15°W 28.6 ft. dist marked T6S R35½E S1 BT.
Set a steel fence post with USFS sign 54-4 attach. Set USFS bearing tree signs on the eight bearing trees facing the corner.

Office of County Surveyor County of Union
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 26 day of July, 1969, at 8 o'clock A m., (signed)
County surveyor by James G Voelz
(COUNTY OFFICIAL) (DEPUTY)

UNION COUNTY
SURVEYOR
Date Received
Date Filed
By
File No. 7638-84 R

E-1

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. E-~~25~~

History of original corner establishment: Corner established in 1881 by Eugene P. McCornack under Contract No. 398.

An 18x8x6 stone was set, from which:
a 24" Pine bears N35°E, 80 lks.,
a 36" Pine bears S20°E, 16 lks.,
a 24" Pine bears S40°W, 64 lks., and
a 36" Pine bears N60°W, 28 lks.

DIAGRAM
T6S
R35 1/2E R36 E

1	6
12	7

Cap is stamped:

COR
T6S
R35 1/2E R36E

S1	S6
S12	S7

ORE LIC 381
1969

Description of corner evidence found:
Found 3" brass cap on 2 3/8" iron pipe rising 8" in mound of stones. Found steel fence post 2 ft. east of corner.

BT's found:
13" D. Fir, good condition, blaze healed, bears N24 1/2°E, 31.7 ft.
Pine stump, badly decayed, no marks, bears N35°E, 80 lks.
Badly decayed Pine, no marks, bears S40°E, 16 lks.
18" D. Fir, good condition, blaze healed, bears S1°E, 35.3 ft.
Badly decayed Pine, no marks, bears S40°W, 64 lks.
16.5" D. Fir, open blaze, bears S77°W, 41.6 ft., scribing visible: T6S R35 1/2E S.
20" dead & down Pine, open blaze bears N60°W, 28 lks., scribed: T6S R35 1/2E S1.
14" P. Pine, partially healed blaze bears N15°W, 28.6 ft., scribing visible: 6S R35 1/2E S1.

Description of monument and accessories re-established to perpetuate the original location of this corner:

The Voltz Section 6 BT is a 13" Douglas Fir instead of Pine listed on certificate and bears N24 1/2°E instead of N17°E. I painted blazes and red bands and signed trees where necessary.

To find corner: from milepost 1.3 on 5125, take river crossing through green gate, left fork 3/4 mile, left fork 1 1/4 mile. Corner is 200 ft. east, visible from road on westerly slope.

Compass Declination: 19 1/2°E
Witness: J. Sutton

I hereby certify that the above described corner monument and/or accessories was ~~perpetuated as hereon~~ perpetuated as hereon described on June 10, 1986.

UNION COUNTY SURVEYOR
Date Received 6-19-86
Date Filed 6-19-86
By G. LANGLITZ, DEPUTY
File No. 90-86 R

REGISTERED PROFESSIONAL LAND SURVEYOR
B. A. Sutton
OREGON
JULY 13, 1979
B. A. SUTTON
1848

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....
..... by .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆U.S. GOVERNMENT PRINTING OFFICE-1983-793-276