CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. V-~~25~~ 1

History of original corner establishment:

Original corner established in 1881 by
Eugene P. McCornack under contract #398.
Set a basalt stone, 30"x20"x8', 20" in ground.
From which:
A 24" Fir bears N50°E, 120 Lks.
A 12" Fir bears S45°E, 125 lks.
A 24" Fir bears S40°W, 80 lks.
A 12" Pine bears N20°W, 130 lks.

DIAGRAM

T6S
R35½E R36E
S25 | S30
S36 | S31

Description of corner evidence found:

Found broken stone, no marks at corner location.
Found the following original bearing trees:
A 27" Doug Fir (live, poor condition), bears N50°E, 120 Lks., blaze healed over from the left side.
A 15½" Fir, dead & down bears S40°W, 80 Lks., open blaze on under side, full scribing visible.
A 14½" dead standing Ponderosa Pine bears N20°W, 130 Lks., opened blaze, 35½E visible.
Found no trace of the Section 31 bearing tree.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the position established from the orig. BT's, I set a 2½"X30" aluminum capped aluminum pipe rising 24" in a mound of stones.
Set steel fencepost 1.2' North in mound of stones.

Cap is stamped:
T6S
R35½E R36E
S25 | S30
S36 | S31
RLS1848
1987

New BT's:
An 8" D. Fir bears N71½°E, 8.4 ft., blazed&scribed T6SR36ES30BT
A 7" D. Fir bears S71°E, 36.2 ft., blazed&scribed T6SR36ES31BT
A 13½" P. Pine bears S24¾°W, 86.7 ft., blazed&scribed: T6SR35½ES36BT
An 8" D. Fir bears N69¼°W, 65.1 ft., blazed&scribed: T6SR35½ES25BT

Painted blazes and attached signs as per **Standard specifications for Cadastral Surveys, USFS** Region 6, March 1982. A ¾" brass disk stamped "RLS 1848" was nailed to the lower end of the blazes.

From Rd. 5185050 follow summit of ridge ¾ mile easterly&northerly to point of ridge where it breaks steeply to the North. Go west 2000 ft., corner is West of sparse mahogany, partially open hillside at the head of two draws, one to the NW, and one to the SW, on a WNW'ly sloping ridgetop.

Compass declination: 20¼°E
Witness: Jeremy Sutton

I hereby certify that the above described corner monument and/or accessories were established as hereon described on June 29, 1987.

REGISTERED PROFESSIONAL LAND SURVEYOR
OREGON
JULY 13, 1979
B. A. SUTTON
1848

UNION COUNTY SURVEYOR
Date Received 8-19-87
Date Filed 8-24-87
By G. LANGLITZ, DEPUTY
File No. 76-87R

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....
..... by .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆U.S. GOVERNMENT PRINTING OFFICE-1983-793-276