

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. R-13

History of original corner establishment: Corner established in 1883 by William B. Barr under Contract No. 492.

- A 24x12x5 stone was set, from which:
 - a 12" Spruce bears N65°E, 20 lks.,
 - a 14" Tamarack bears S40°E, 14 lks.,
 - a 12" Pine bears S40°W, 20 lks., and
 - a 12" Pine bears N10°W, 24 lks.

DIAGRAM
T6S R36E
21 22
28 27
UNION COUNTY
SURVEYOR
Date Received <u>6-19-86</u>
Date Filed <u>6-19-86</u>
By <u>G. LANGLITZ, DEPUTY</u>
File No. <u>87-86 R</u>

Description of corner evidence found:
Found original stone firmly in place.

- BT's found:
- 15.5"x9" double spruce, 15" part with open blaze, faint scribing, bears N71 1/2°E, 12.9 ft. (Original notes say N65°E, 20 lks.)
 - 10.5" dead standing western larch bears S38°E, 9.3 ft., open blaze scribing visible: T6S R36E S27 BT (Original says S40°E)
 - 8" Pine stump 5 ft. high, open blaze, scribing visible: T6 R BT bears S37°W, 13.8 ft. (Original notes say S40°W, 20 lks.)
 - Badly decayed L. Pine, open blaze, scribing visible: BT bears N10°W, 24 lks.

Description of monument and accessories | established to perpetuate the original location of this corner: Cap is stamped:

- Set 2.5"x30" aluminum capped aluminum pipe rising 3" with original stone buried along north side. No other stones available.
- Set steel fence post 3 ft. north of corner.

T6S R36E
 S21 | S22
 S28 | S27
 RLS 1848
 1986

- New BT's:
- 11.5" D. Fir bears S32 1/2°E, 15.0 ft., blazed & scribed: T6S R36E S27 BT.
 - 12.5" Spruce bears S38 3/4°W, 28.3 ft., blazed & scribed: T6S R36E S28 BT.
 - 7.5" W. Fir bears N41 1/4°W, 24.5 ft., blazed & scribed: T6S R36E S21 BT.

Attached 3/4" brass washer marked LS 1848 to blazes. Painted blazes and attached signs as per Standard Specifications for Cadastral Surveys, USFS Region 6, March 1982.

To find corner: Go to the south end of 5135089. Cross the earthfill dam. Upstream about 400 ft. I painted a red band & tagged a 12" spruce on the east bank of the creek. Corner is 200 ft. east up the hill.

Compass Declination: 19 1/2°E
Witness: J. Sutton

I hereby certify that the above described corner monument and/or accessories was perpetuated as hereon described on June 3, 1986.



Office of..... County of.....
 State of....., I hereby certify that the within instrument was filed in this office
 for record on the..... day of....., 19.....
 by.....
 (COUNTY OFFICIAL) (DEPUTY)