


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

SURVEYED BY: W.B. BARR, 1885, CONTRACT NO. 516

Set a post.

A Tamarack 24" in diam. bears S 70 W, 1 ch. 18 lks. Dist.



Description of corner evidence found:

Found mound of stones at a fence corner. This corner fence post and stones fit the record distance to the standard corner of sections 34 and 35.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a USFS 3 1/4" aluminum capped pipe, cap marked per diagram, 16" in the ground with a 3' x 3' mound of stone, from which:

A pine, 9" diam., bears N.30°11'E., 27.77', with a 6" x 6' blaze, scribed "X BT".

A pine, 10" diam., bears N.35°58'W., 21.80', with a 8" x 5" blaze, scribed "X BT".

A pine, 11" diam., bears S.66°43'W., 57.44', with a 21" x 5" blaze, scribed "T6S R41E S3 CC BT".

A pine, 8" diam., bears S.43°11'E., 61.97', with a 20" x 4" blaze, scribed "T6S R41E S2 CC BT".

A 6' x 4' x 4' stone, bears S.E. 3½ ft.



REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY
WITNESS TO MONUMENT: DAVID SUTHERLAND
BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.
BASIS OF BEARINGS WAS A GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.

Office of _____ County of _____
State of _____ I hereby certify that the within instrument was filed in this office
for record on the ____ day of _____, 19____
_____ by _____
(COUNTY OFFICIAL) (DEPUTY)

