


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This corner was not established by a previous survey.



Description of corner evidence found:

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a USFS 3¼" aluminum capped pipe, cap marked per diagram, 22" in the ground, with a mound of stone to cap.

- A pine, 10" in diam., bears N.41°45'W., 19.30', scribed "¼S1BT".
- A pine, 6" in diam., bears N.52°56'E., 12.93', scribed "¼S1BT".
- A pine, 8" in diam., bears S.16°26'E., 39.70', scribed "¼S1BT".
- A pine, 10" in diam., bears S.62°20'W., 40.96', scribed "¼S1BT".

REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY
 WITNESS TO MONUMENT: DAVID SUTHERLAND
 BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.
 BASIS OF BEARINGS WAS A GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.

UNION COUNTY
SURVEYOR

Date Received 10/28/98
 Date Filed 10/31/98
 by R. ROBINSON, DEPUTY
 File No. 109-1998R

REGISTERED
PROFESSIONAL
LAND SURVEYOR

M & Stoll 9/98

OREGON
JULY 15, 1983
RONALD E. STOLL
2058

Office of _____
 State of _____ I hereby certify that the within instrument was filed in this office
 for record on the ____ day of _____, 19____
 _____ by _____
 (COUNTY OFFICIAL) (DEPUTY)