


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

SURVEYED BY: W.B. BARR, 1885, CONTRACT NO. 516

40.00 Top hill, setstone 20 x 10 x 6 ins., for 1/4 sec. cor., from which:

- A pine, 24 ins. diam., bears N.56°E., 55 lks. dist.
- A pine, 36 ins. diam., bears N.40°W., 68 lks. dist.



Description of corner evidence found:

No evidence of original monument found.

REGISTERED
 PROFESSIONAL
 LAND SURVEYOR

RMS Stoll 9/98

OREGON
 JULY 15, 1983
 RONALD E. STOLL
 2058

Description of monument and accessories I established to perpetuate the original location of this corner:

At a proportionate position, set a USFS 3 1/4" aluminum capped pipe, cap marked per diagram, 4" in the ground with mound of stone to cap, from which:

- A fir, 18" in diam., bears S.85°50'W., 81.0', scribed "1/4S2BT"
- A pine, 12" in diam., bears N.51°40'W., 28.9', scribed "1/4S2BT".
- A pine, 9" in diam., bears S.28°30'E., 15.0', scribed "1/4S1BT".
- A pine, 16" in diam., bears S.14°00'W., 47.0', scribed "1/4S2BT".

REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY

WITNESS TO MONUMENT: ERIC GREEN

BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.

BASIS OF BEARINGS WAS A GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.

Office of _____ County of _____
 State of _____ I hereby certify that the within instrument was filed in this office
 for record on the _____ day of _____, 19____
 _____ by _____
 (COUNTY OFFICIAL) (DEPUTY)

WAGON COUNTY
 SURVEYOR

Date Filed 10/31/98

By R. ROBINSON, DEPUTY

File No. 123-19781