


J-13 T6S R41E

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

2 1/2" IRON POST 28" LONG 10" IN GROUND AND
IN A MOUND OF STONE 4' BASE TO TOP



ACCESSORIES: DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

- A Pine 8" BRS, N 70 1/2° E 109 1/2 LKS MKD T6S R41E S10 BT
- A Pine 12" BRS S 62 1/2° E 112 LKS MKD T6S R41E S15 BT
- A Pine 13 BRS N 27 1/2° W 58 1/2 LKS MKD T6S R41E S9 BT

Work Done By S. ALBRIGHT Title CADASTRAL SURVEYOR Date 10-5-21 State Registration No. or Agency BLM 10
 Certified Cor. Record Prepared? Yes No Filed At: _____ Date _____ 11

REMARKS

Index File No. T. R. M. Tract or Surv. No. Cor. 12
13

UNION COUNTY SURVEYOR	
Date Received	_____
Date Filed	<u>12-23-87</u>
By	<u>G. LANGLITZ, DEPUTY</u>
File No.	<u>384-87R</u>

J-13

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

SURVEYED BY: W.B. BARR, 1885, CONTRACT NO. 516

SURVEYED BY: S. ALBRIGHT, 1971, CONTRACT NO. 350

The cor. of secs. 9, 10, 15, and 16, monumented with the original basalt stone, 20 x 8 x 6 ins., loosely set 4 ins. in the ground, marked with 3 grooves on E. face and 4 notches on S. edge, from which the original bearing trees:

A root hole, bears N.32°E., 80 lks. dist., with a down ponderosa pine alongside, size indeterminate, no marks visible. (Record, N.40°E.)

A decayed ponderosa pine snag, 38 ins. diam., bears S.25°E., 38 lks. dist., with fragmentary scribe marks visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, directly over X marked on bedrock, and in a mound of stone, 4 ft. base, to top, with brass cap

from which new bearing trees:

- A ponderosa pine, 8 ins. diam., bears N.70½°E., 109½ lks. dist. mkd. T6S R41E S10 BT
- A ponderosa pine, 12 ins. diam., bears S.62½°E., 112 lks. dist. mkd. T6S R41E S15 BT
- A ponderosa pine, 13 ins. diam., bears N.27½°W., 58½ lks. dist. mkd. T6S R41E S9 BT

Deposit corner stone alongside iron post

Description of corner evidence found:


Found a 3" diam. BLM brass capped pipe, cap marked per diagram, 17" above the ground, with a 5' collar of stones, from which:

- A pine, 19" in diam., bears N.27°15'W., 38.73', healed blaze.
- A pine, 12" in diam., bears N.70°30'E., 72.61', scribed "T6SR41ES10BT".
- A pine, 14" in diam., bears S.62°55'E., 73.29', scribed "T6SR41ES15BT".
- A dead pine snag, 36" in diam., bears S.25°20'E., 25.67', with no viable marks.

Description of monument and accessories I established to perpetuate the original location of this corner:

A pine, 18" in diam., bears S.35°30'E., 90.69', scribed "T6SR41ES15BT".

REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY
WITNESS TO MONUMENT: DAVID SUTHERLAND
BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.
BASIS OF BEARINGS WAS A GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.



CLATSOP COUNTY
SURVEYOR

Date Received 10/28/98
Date Filed 10/31/98
by R. Robinson Deputy
File No. 171-1998R

Office of _____ County of _____
State of _____ I hereby certify that the within instrument was filed in this office
for record on the ____ day of _____, 19____
_____ by _____
(COUNTY OFFICIAL) (DEPUTY)

REGISTERED
PROFESSIONAL
LAND SURVEYOR

R. E. Stoll 9/98

OREGON
JULY 15, 1923
RONALD E. STOLL
2058

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


J-13

History of original corner establishment:

SURVEYED BY: W.B. BAR, 1885, CONTRACT NO. 516

SURVEYED BY: S. ALBRIGHT, 1971, CONTRACT NO. 350

The cor. of secs. 9, 10, 15, and 16, monumented with the original basalt stone, 20 x 8 x 6 ins., loosely set 4 ins. in the ground, marked with 3 grooves on E. face and 4 notches on S. edge, from which the original bearing trees:



A root hole, bears N.32°E., 80 lks. dist., with a down ponderosa pine alongside, size indeterminate, no marks visible. (Record, N.40°E.)

A decayed ponderosa pine snag, 38 ins. diam., bears S.25°E., 38 lks. dist., with fragmentary scribe marks visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, directly over X marked on bedrock, and in a mound of stone, 4 ft. base, to top, with brass cap

from which new bearing trees:

A ponderosa pine, 8 ins. diam., bears N.70½°E., 109½ lks. dist. mkd. T6S R41E S10 BT

A ponderosa pine, 12 ins. diam., bears S.62½°E., 112 lks. dist. mkd. T6S R41E S15 BT

A ponderosa pine, 13 ins. diam., bears N.27½°W., 58½ lks. dist. mkd. T6S R41E S9 BT

Deposit corner stone alongside iron post

Description of corner evidence found:

Found a 3" diam. BLM brass capped pipe, cap marked per diagram, 17" above the ground, with a 5' collar of stones, from which:

A pine, 19" in diam., bears N.27°15'W., 38.73', healed blaze.

A pine, 12" in diam., bears N.70°30'E., 72.61', scribed "T6SR41ES10BT".

A pine, 14" in diam., bears S.62°55'E., 73.29', scribed "T6SR41ES15BT".

A dead pine snag, 36" in diam., bears S.25°20'E., 25.67', with no visible marks.

Description of monument and accessories I established to perpetuate the original location of this corner:

A pine, 18" in diam., bears S.35°30'E., 90.69', scribed "T6SR41ES15BT".

REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY

WITNESS TO MONUMENT: DAVID SUTHERLAND

BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG

ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.

BASIS OF BEARING WAS GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.

UNION COUNTY SURVEYOR	
Date Received	1/4/06
Date Filed	9/9/06
By	R. Robinson, Deputy
File No.	017-2006R

REGISTERED PROFESSIONAL LAND SURVEYOR

OREGON JULY 15, 1983 RONALD E. STOLL 2058
--

Office of _____ County of _____
State of _____ I hereby certify that the within instrument was filed in this office
for record on the ____ day of _____, 19____
_____ by _____
(COUNTY OFFICIAL) (DEPUTY)

BO

T6S41E13

T. 6 S., R. 41 E., Willamette Meridian, Oregon

CHAINS

The following field notes describe the remonumentation of certain original corner points, township 6 south, range 41 east, Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group Number 350 Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points, with New Accessories when Needed".

The remonumentation of original corner points was made at the request of the United States Forest Service in conjunction with their Land Line Location Program.

The mean magnetic declination is 20° E.

Subdivision, T. 6 S., R. 41 E.,
Willamette Meridian, Oregon

(Remonumenting corners established by John W. Stone,
in 1875)

The cor. of secs. 11, 12, 13, and 14, determined at record bearing and distance from the only remaining original bearing tree:

A sawed ponderosa pine stump, 42 ins. diam., bears S. 70° E., 57 lks. dist. with scribe marks BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S R 41 E
S 11 | S 12
S 14 | S 13
1971

from which new bearing trees

A ponderosa pine, 13 ins. diam., bears N. 61½° E., 47½ lks. dist., mkd. T6S R41E S12 BT.

A ponderosa pine, 13 ins. diam., bears S. 31° E., 56½ lks. dist., mkd. T6S R41E S13 BT.

A ponderosa pine, 7 ins. diam., bears S. 71½° W., 119 lks. dist., mkd. T6S R41E S14 BT.

A ponderosa pine, 12 ins. diam., bears N. 67° W., 85 lks. dist., mkd. T6S R41E S11 BT.

Set 5 ft. steel fence post alongside iron post.

Corner falls at intersection of old fences, extending N., S., and E.

The cor. of secs. 9, 10, 15, and 16, monumented with the original basalt stone, 20 x 8 x 6 ins., loosely set 4 ins. in the ground, marked with 3 grooves on E. face and 4 notches on S. edge, from which the original bearing trees:

A root hole, bears N. 32° E., 80 lks. dist., with a down ponderosa pine alongside, size indeterminate, no marks visible. (Record, N. 40° E.)

UNION COUNTY
SURVEYOR

Date Received

3/15/13

Date Filed

3/15/13

By

J. S. L. DEPUTY

File No.

400-2013R

Remonumentation of Certain Original Corner Points,
T. 6 S., R. 41 E., Willamette Meridian, Oregon

CHAIN

A decayed ponderosa pine snag, 38 ins. diam., bears S. 25° E., 38 lks. dist., with fragmentary scribe marks visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, directly over X marked on bedrock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T 6 S R 41 E
S 9 | S 10
S 16 | S 15
1971

from which new bearing trees

A ponderosa pine, 8 ins. diam., bears N. 70½° E., 109½ lks. dist., mkd. T6S R41E S10 BT.

A ponderosa pine, 12 ins. diam., bears S. 62½° E., 112 lks. dist., mkd. T6S R41E S15 BT.

A ponderosa pine, 13 ins. diam., bears N. 27½° W., 58½ lks. dist., mkd. T6S R41E S9 BT.

Deposit corner stone alongside iron post.

The cor. of secs. 3, 4, 9, and 10, determined at record bearing and distance from the only remaining original bearing tree:

A ponderosa pine, 28 ins. diam., bears S. 30° E., 10 lks. dist., with scribe marks S10 BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 6 S R 41 E
S 2 | S 3
S 9 | S 10
1971

from which new bearing trees

A fir, 11 ins. diam., bears N. 46° E., 46 lks. dist., mkd. T6S R41E S3 BT.

A ponderosa pine, 10 ins. diam., bears S. 79° E., 32 lks. dist., mkd. T6S R41E S10 BT.

A fir, 14 ins. diam., bears S. 71½° W., 43 lks. dist., mkd. T6S R41E S9 BT.

A fir, 12 ins. diam., bears N. 19½° W., 55 lks. dist., mkd. T6S R41E S4 BT.

UNION COUNTY
SURVEYOR

Date Received 3/15/13

Date Filed 3/15/13

By [Signature] DEPUTY

File No. 400-2013R