

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

DIAGRAM
T 6 S R 42 E

C ¼

S 21

LS 2058
1992

Description of corner evidence found:

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 3" diam. U.S.F.S aluminum capped pipe, 30" long, with magnet, 18" in the ground with mound of stone to cap, from which:

- A tamarack, 21" diam., bears N.14°59'W., 79.60', scribed "C¼ S21 BT".
- A tamarack, 22" diam., bears N.80°02'E., 14.47', scribed "C¼ S21 BT".
- A pine, 14" diam., bears S.19°37'E., 45.90', scribed "C¼ S21 BT".
- A pine, 15" diam., bears S.71°30'W., 62.08', scribed "C¼ S21 BT".

UNION COUNTY SURVEYOR

Date Received 8/18/94

Date Filed 10/22/94

By [Signature]

File No. 058-1994R.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

[Signature]

OREGON
JULY 15 1983
RONALD E. STOLL
2058

Office of _____ County of _____
 State of _____ I hereby certify that the within instrument was filed in this office
 for record on the ____ day of _____, 19__
 _____ by _____
 (COUNTY OFFICIAL) (DEPUTY)

DD

P-11